



## Features:

- Create content on your PC and publish it to the Avelin via the Ethernet
- Content includes text, images, Adobe Flash, up to 4 regions of crawling text, and video
- Controlled remotely via bundled Composer software
- 3 Composite and 1 S-Video input for standard definition video pass through and switching
- High resolution display support for widescreen displays
- Higher performance for Portrait displays and complex Flash presentations (AV400P only)

## Specifications

### I/O

<b>Video Outputs</b>	1 VGA
<b>Video Inputs</b>	3 Composite, 1 S-Video
<b>Audio Inputs</b>	1 x 1/8" Stereo, 1 x 1/8" Mono
<b>Audio Outputs</b>	1 x 1/8" Stereo
<b>Other Ports</b>	10/100 Ethernet, 2 x Serial, 2 x USB, 2 x PS/2
<b>Video Modes</b>	<u>Standard (4:3):</u> 640x480, 800x600, 1024x768, 1280x1024 <u>Widescreen (16:9):</u> 848x480, 852x480, 1066x600, 1360x768, 1280x720, 1280x768, 1376x768

### Content

<b>Text</b>	True type fonts supported
<b>Images</b>	JPG, JPG2000, PCD, TIFF, BMP, RLE, DIB, EPS, GIF, PNG, TGA, IMG, DXF, PCX, DCX, and WMF Clipart
<b>Motion</b>	Flash (SWF, FLV), MPEG (with optional Adtec MPEG Player), Analog Video Sources (DVD, VHS, etc.)
<b>Overlay Regions</b>	4 regions for customizable static or crawling text/graphics
<b>Transitions</b>	38 High-quality page/slide transitions
<b>Page Capacity</b>	10,000+ pages (35 GB)

### Recommended Flash Settings

<b>Data Rate</b>	768 Kbps
<b>Frame Size</b>	480 (W) x 360 (H) (for FLV)
<b>Frame Rate</b>	20 Frames/second (Maximum)
<b>Min. Quality</b>	50%

### Composer Software

<b>OS Requirements</b>	Windows 2000/XP/Vista
<b>Publish Methods</b>	Ethernet, Serial, Modem, USB
<b>Models</b>	400, Professional

### Mechanical/Environmental

<b>Dimensions</b>	19"(W) x 16.5"(D) x 3.5"(H) (w/rack ears) 17"(W) x 16.5"(D) x 3.5"(H) (no rack ears)
<b>Form Factor</b>	2U Rack Mounted Case
<b>Power Draw</b>	0.62A (Max 0.75A), 74.4W (Max 90W)


### Optional Components

- Adtec MPEG Player
- Infra-Red VHS/DVD Control
- Live Weather Display System
- NOAA Weather data feed
- News RSS Feeds: National, World, Business, Entertainment
- Other RSS Feeds: Sports, Financial, Custom Stocks
- E-Blast Remote Access software
- EZ-Stream Database Integration software
- Artwork Expansion packages
- VGA over Cat5 Display option
- Analog Modem transfer option
- USB removable media transfer option
- Extended Warranty

### Packing List

- Avelin Main System Unit
- Control Keypad
- Power Cord
- S-Video Cable
- Null Modem Serial Cable
- Avelin Composer CD-ROM
- Avelin Training DVD
- 2x 1/8" Audio Cable
- User Manual
- Warranty/Registration Card

Connection Diagram (various uses)



Rear Panel



# Comparison Chart

Product	Video Outputs	Video Inputs	Max Resolutions	Audio Inputs	Content	Size	Page Capacity
<b>Aavelin (AV100)</b>	VGA, Composite, S-Video	None	4:3 – 800x600, 16:9 – 1066x600	2 x 1/8" Stereo 1 x 1/8" Mono	Text, Images, Shapes, Flash, crawl regions	19" x 16.5" x 3.5" or 17" x 16.5" x 3.5"	10,000+ (15GB)
<b>Aavelin RT (AV200)</b>	VGA, Composite, S-Video	3 x Composite, 1 x S-Video	4:3 – 800x600, 16:9 – 1066x600	2 x 1/8" Stereo 1 x 1/8" Mono	Text, Images, Shapes, Flash, Video pass through, crawl regions	19" x 16.5" x 3.5" or 17" x 16.5" x 3.5"	10,000+ (15GB)
<b>Aavelin HD (AV400)</b>	VGA	3 x Composite, 1 x S-Video	4:3 – 1280x1024 16:9 – 1376x768	1 x 1/8" Stereo 1 x 1/8" Mono	Text, Images, Shapes, Flash, Video pass through, crawl regions	19" x 16.5" x 3.5" or 17" x 16.5" x 3.5"	10,000+ (15GB)
<b>Aavelin HDP (AV400P)</b>	VGA	3 x Composite, 1 x S-Video	4:3 – 1280x1024 16:9 – 1376x768	1 x 1/8" Stereo 1 x 1/8" Mono	Text, Images, Shapes, Flash, Video pass through, crawl regions	19" x 16.5" x 3.5" or 17" x 16.5" x 3.5"	10,000+ (15GB)
<b>Aavelin 1080P (AV1080P)</b>	VGA, DVI	TBA	4:3 – 1280x1024 16:9 – 1920x1080	1 x 1/8" Stereo 1 x 1/8" Mono	Text, Images, Shapes, Flash, crawl regions	19" x 16.5" x 3.5" or 17" x 16.5" x 3.5"	10,000+ (15GB)
<b>SignMate (AV800)</b>	VGA, DVI	TBA	4:3 – 1280x1024 16:9 – 1376x768	1 x 1/8" Mono	Text, Images, Shapes, Flash, crawl regions	8.7" x 5.3" x 1.7"	10,000+ (15GB)
<b>VIP (VIP5)</b>	VGA	None	4:3 – 1024x768 16:9 – 1280x768	None	Text, Images, Shapes	6.75" x 5" x 1.5"	70-150 (64MB)
<b>VIP TV (VIP6)</b>	Composite	None	4:3 – 1024x768, 16:9 – 1066x600	None	Text, Images, Shapes	6.75" x 5" x 1.5"	100-150 (64MB)
<b>Memo (MEMO1)</b>	VGA, Composite, S-Video	None	4:3 – 800x600, 16:9 – 1066x600	None	Text, Images, static region	19" x 16.5" x 3.5" or 17" x 16.5" x 3.5"	10,000+ (15GB)

## Notes:

1. All units can be controlled remotely via Ethernet
2. Units with Flash capability include SWF and FLV using Flash Player 7
3. Crawl and Static Regions are horizontal lines at the top or bottom of the screen and can contain text and small graphics.